777 PØ3 MAR 24 'Ø6 17:58

+860-527-5029 ALIX YALE & RISTAS

Appl. No.: 10/783,633

Amdt. dated March 24, 2006

Reply to Office Action of January 20, 2006

This listing of claims will replace all prior versions and listings of claims in the application.

## Claim Listing:

- 1. (currently amended) A handle for use with cookware, the cookware having a wall and an attachment member, wherein the handle is pivotally mountable to the attachment member about a horizontal axis for movement between a lifting position wherein the handle projects transversely from the cookware and a stored position wherein the handle is approximately parallel to the wall of the cookware; and a catch for positioning and holding the handle relative to the cookware, the catch including an elastically resilient member having a detent for engaging a recess positioned with the handle wherein the handle includes a cam for raising an edge of the lid when the handle is pivoted in a direction of the stored position.
- 2. (previously presented) The handle of claim 1 wherein the catch is released by force applied to the handle.
- 3. (cancelled)
- 4. (currently amended) A handle for use with cookware having a base and a lid defining a cooking chamber, the base including a wall and an attachment member, wherein the handle is pivotally mountable to the attachment member about a horizontal

777 P04 MAR 24 '06 17:59

+860-527-5029 ALIX YALE & RISTAS

Appl. No.: 10/783,633

Amdt. dated March 24, 2006

Reply to Office Action of January 20, 2006

axis for movement between a lifting position wherein the handle projects transversely from

the cookware and a stored position wherein the handle is approximately parallel to the wall

of the cookware and a catch for positioning and holding the handle relative to the

cookware, the catch including an elastically resilient member having a detent for

engaging a recess positioned with the handle wherein the handle includes a cam for

raising an edge of the lid when the handle is pivoted in a direction of the stored position.

5. (cancelled)

6. (currently amended) The handle of claim [[5]] 4 wherein the cam is a curved surface

eccentric to the horizontal axis.

7. (previously presented) The handle of claim 4 wherein the catch is released by force

applied to the handle.

8. (canceled)

9. (currently amended) A cookware item comprising:

a base having a wall and an attachment member,

a lid locatable on the base for defining a cooking chamber, and

a handle pivotally mounted to the attachment member about a horizontal axis and

movable between a lifting position wherein the handle projects transversely from the

3

PAGE 4/7 \* RCVD AT 3/24/2006 4:52:54 PM [Eastern Standard Time] \* SVR:USPTO-EFXRF-5/15 \* DNIS:2738300 \* CSID:+860 527 5029 \* DURATION (mm-ss):02-20

+860-527-5029 ALIX YALE & RISTAS

777 P05 MAR 24 '06 17:59

Appl. No.: 10/783,633

Amdt. dated March 24, 2006

Reply to Office Action of January 20, 2006

cookware and a stored position wherein the handle is approximately parallel to the wall of the cookware, and

a catch for positioning and holding the handle relative to the cookware, the catch including an elastically resilient member having a detent for engaging a recess positioned with the handle and wherein the handle includes a cam for raising an edge of the lid when the handle is pivoted in a direction of the stored position.

- 10. (cancelled)
- 11. (currently amended) The cookware of claim [[10]] 9 wherein the cam is a curved surface eccentric to the horizontal axis.
- 12. (previously presented) The cookware of claim 9 wherein the catch is released by force applied to the handle.
- 13. (cancelled)
- 14. (currently amended)A cookware item comprising: a base and a lid defining a cooking chamber, the base including a wall and an attachment member; a handle pivotally mountable to the attachment member about a horizontal axis for movement; a disc having four recesses evenly spaced about its periphery; and a catch for positioning and holding the handle relative to the cookware in at least two positions, said catch comprising an elastically resilient member having a pair of detents for engaging a pair of diametrically opposed recesses positioned with the handle for each catch position wherein said

Appl. No.: 10/783,633

Amdt. dated March 24, 2006

Reply to Office Action of January 20, 2006

elastically resilient member is substantially U shaped and has two legs that are formed into detents.

- 15. (cancelled)
- 16. (cancelled)
- 17. (presently amended) The cookware of claim [[16]] 14 wherein said detents engage said recesses located on the periphery of said disc.
- 18. (previously presented) The cookware of claim 17 wherein said recesses define positions of said handle relative to the wall of said cookware.
- 19. (previously presented) The cookware of claim 18 wherein said catch is released by force applied to the handle.
- 20. (previously presented) The cookware of claim 19 wherein said recesses define three handle positions.